

09-18-00

A

# FISH & RICHARDSON P.C.

September 15, 2000

Attorney Docket No.: 10559/195001/P8367

**Box Patent Application**  
Commissioner for Patents  
Washington, DC 20231

Presented for filing is a new original patent application of:

Applicant: FERNANDO C.M. MARTINS

Title: GESTURE RECOGNITION

Enclosed are the following papers, including those required to receive a filing date under 37 CFR 1.53(b):

	Pages
Specification	20
Claims	7
Abstract	1
Declaration	[To be Filed at a Later Date]
Drawing(s)	8

Enclosures:  
— Postcard.

There are 30 total claims, 4 of which are independent.

Basic filing fee	\$0
Total claims in excess of 20 times \$18	\$0
Independent claims in excess of 3 times \$78	\$0
Fee for multiple dependent claims	\$0
Total filing fee:	\$0

## CERTIFICATE OF MAILING BY EXPRESS MAIL

Express Mail Label No. EL558601719US

I hereby certify that this correspondence is being deposited with the United States Postal Service as Express Mail Post Office to Addressee with sufficient postage on the date indicated below and is addressed to the Commissioner for Patents, Washington, D.C. 20231.

Date of Deposit September 15, 2000

Signature *Derek W. Norwood*

Derek W. Norwood  
Typed or Printed Name of Person Signing Certificate

4350 La Jolla Village Drive  
Suite 500  
San Diego, California  
92122

Telephone  
858 678-5070

Facsimile  
858 678-5099

Web Site  
www.fr.com

jc907 U.S. PTO  
09/662679  
09/15/00

09/15/00  
JC916 U.S. PTO

Frederick P. Fish  
1855-1930

W.K. Richardson  
1859-1951



BOSTON  
DALLAS  
DELAWARE  
NEW YORK  
SAN DIEGO  
SILICON VALLEY  
TWIN CITIES  
WASHINGTON, DC

09562679-091500

FISH & RICHARDSON P.C.

Commissioner for Patents  
September 15, 2000  
Page 2


No filing fee is being paid at this time. If this application is found to be incomplete, or if a telephone conference would otherwise be helpful, please call the undersigned at (858) 678-5070.

Kindly acknowledge receipt of this application by returning the enclosed postcard.

Please send all correspondence to:

SCOTT C. HARRIS  
Fish & Richardson P.C.  
Customer Number: 20985  
4350 La Jolla Village Drive, Suite 500  
San Diego, CA 92122

Respectfully submitted,



Scott C. Harris  
Reg. No. 32,030  
Enclosures  
SCH/rpi  
10053723 doc

005760 929990

APPLICATION  
FOR  
UNITED STATES LETTERS PATENT

TITLE: GESTURE RECOGNITION  
APPLICANT: FERNANDO C.M. MARTINS

CERTIFICATE OF MAILING BY EXPRESS MAIL


Express Mail Label No. EL558601719US

I hereby certify that this correspondence is being deposited with the United States Postal Service as Express Mail Post Office to Addressee with sufficient postage on the date indicated below and is addressed to the Commissioner for Patents, Washington, D.C. 20231.

September 15, 2000

Date of Deposit

Signature



Derek W. Norwood

Typed or Printed Name of Person Signing Certificate

09553634.094500  
005760.029950

## **GESTURE RECOGNITION**

### **BACKGROUND**

This disclosure relates to gesture recognition.

Computers, game consoles, personal digital assistants,  
5 and other information appliances typically include some type  
of user interface through which inputs and outputs pass.

Inputs from the user are often delivered through a cable  
from a keyboard, a mouse, a joystick, or other controller.  
The user actuates keys, buttons, or other switches included on  
10 the controller in order to provide input to the information  
appliance. The action a user takes in order to provide input  
to an information appliance, such as pressing a button, is  
referred to here as an "input action."

In some applications, it may be desirable for an input  
15 action to be driven by a particular human gesture.  
Specialized input devices can be used in such applications so  
that the user can provide command and control inputs by  
performing a particular gesture in direct physical contact  
with the input device. For example, in a dance competition  
20 game, the game prompts the user to "perform" various dance  
moves. A pressure sensitive pad is typically provided so that  
the user can perform a dance move by tapping a specified

portion of the pressure sensitive pad with one of the user's feet. In this way, the input action (that is, tapping a portion of the pressure sensitive pad) captures an aspect of a dance move. Another example is a music creation program in which a user can hit a MIDI drum pad with drumsticks in order to simulate playing the drums.

Other approaches to supplying input to an information appliance may make use of gesture recognition technology. In one approach, motion capturing sensors, e.g, body suits or gloves are attached to the user to measure the user's movements. These measurements are then used to determine the gesture that the user is performing. These devices are often expensive and intrusive. Gesture recognition makes use of pattern recognition technology. Generally, such an approach involves capturing video of a user performing various actions, temporally segmenting the video into video clips containing discrete gestures, and then determining if each video clip contains a predefined gesture from a gesture vocabulary. For example, one potential application of such gesture recognition technology is to recognize gestures from the American Sign Language. Such gesture recognition technology typically requires the video to be manually segmented into video clips, which makes such conventional gesture recognition technology less than fully automatic.

## DESCRIPTION OF DRAWINGS

FIG. 1 is a flow diagram of a gesture recognition process.

FIG. 2 is a flow diagram of a process of segmenting the  
5 video data into video clips based on timing data.

FIG. 3 is a flow diagram of a process of determining the probability that a video clip contains a predefined gesture.

FIG. 4 is a flow diagram of a process for determining if  
10 the video clip contains a gesture contained in the gesture vocabulary.

FIG. 5 is a block diagram of a system that can be used to implement the gesture recognition process shown in FIG. 1.

FIG. 6 is a block diagram of an embodiment that is  
15 designed using this technology; FIGS. 7A-7B show examples of a game screen shots from the system shown in FIG. 6.

## DETAILED DESCRIPTION

FIG. 1 is a flow diagram of a gesture recognition process  
100. Process 100 includes segmenting video data into video  
clips based on timing data (block 102). The timing data is  
20 used to define a window within which a user is expected to  
perform a single desired gesture. The video data is segmented  
so that each video clip contains the video data for a single  
window. In one embodiment, the timing data is a function of

an audio signal having a beat. As used here, beat refers to any audibly perceptible semi periodic pulse contained within an audio signal. In such an embodiment, the user is expected to perform various predefined gestures "on the beat." That is, the window in which the user is expected to perform each gesture is defined by the beats of the audio signal. For example, the window can be defined so as to require the user to perform a desired predefined gesture within one second after a beat is played by a speaker. Alternatively, the window can be defined so as to require the user to perform the desired gesture in a one second time period starting one-half second before a beat is played by the speaker and ending one-half second after the beat. Another alternative is to define the window by a pair of adjacent beats are the audio signal.

Because the user is expected to perform each gesture within a window defined by the timing data, the process 100 can automatically segment the video data into video clips based on the timing data; conventional manual techniques for segmenting video data need not be used. Consequently, process 100 can be used to segment video data into video clips reliably and in real time.

The process 100 also includes determining the probability that the video clip contains a predefined gesture (block 104). Any conventional pattern recognition techniques can be used to

determine the probability that the video clip contains a predefined gesture. For example, Hidden Markov Models ("HMMs"), neural networks, and Bayesian classifiers can be used.

5 Typically, the video clip is compared to multiple predefined gestures that are included in a gesture vocabulary. For each predefined gesture in the gesture vocabulary, the probability that the video clip contains that gesture is determined. The probabilities can then be compiled in a  
10 gesture probability vector. By keeping the predefined gesture vocabulary relatively small, the performance of the pattern recognition techniques can be improved. However, a gesture vocabulary of various sizes can be used.

The window can also be defined by a pair of subsequent  
15 beats.

FIG. 3 is a flow diagram of a process 300 of determining the probability that a video clip contains a predefined gesture. First, movement of the user's body is identified and tracked for each frame in the video clip (block 302). In one  
20 embodiment, the moving regions in each video frame in the video clip are identified A three frame difference classifier can be used to identify the moving regions in each video frame in the video clip. For a given video frame in the video clip (referred to here as the current frame), a pixel-by-pixel

comparison of the current frame and the immediately preceding frame, and a pixel-by-pixel comparison of the current frame and the immediately following frame, is performed. For a given pixel in the current frame, the difference between the color of that pixel and the color of the corresponding pixel in the immediately preceding frame is determined. Also, for a given pixel in the current frame, the difference between the color of that pixel and the color of the corresponding pixel in the immediately following frame is determined. If both differences exceed a predefined tolerance for a given pixel, that pixel is considered to be a moving pixel. The moving pixels in the current frame are then clustered into moving regions (also referred to as "blobs") using morphological image processing operations. The morphological image processing operations operate to remove noise from the blobs. Alternatively, other motion estimation and clustering techniques can be used to identify the moving regions in each frame of the video clip.

Alternatively, one or more objects associated with the user can be identified and tracked in each frame in the video clip. For example, the user can wear colored wrist bands and/or a head band. The movements of the wrist and head bands can then be identified and tracked using a conventional object tracker. Such an object tracker is initialized by first

capturing data of the user wearing the wrist and/or head bands and then having the user (or other operator) manually identify the wrist and/or head bands in the video data. For example, a video camera can capture a single video frame of the user

5 wearing the wrist and/or head bands. Then the user can manipulate a mouse or other input device in order to identify the wrist and/or hand bands within the captured video frame. Then, the size and average color of the regions of the video corresponding to the wrist and/or head bands are calculated.

10 Also, the center of each region can be determined.

Conventional object tracking techniques can then be used to track the identified wrist and/or head bands within a video clip. For example, for each frame in a video clip, a region corresponding to each tracked object (e.g., a wrist and/or  
15 head band) can be identified by locating a region in the frame having a size and average color that is similar to the size and average color calculated for the tracked object during initialization. Then, the XY coordinates of the center of the identified region can be determined. Next, feature vectors  
20 are generated for each video frame (block 304). A feature vector is an array of numbers that describes the shape, location, and/or movement of one or more moving regions in each frame. Feature vectors can be generated in conventional ways. The data contained in the feature vectors depends on

the particular techniques used to track and identify the user's movements. For example, if the user's movements are tracked by identifying moving blobs in each frame of the video clip, the feature vectors can include position information, motion information, and blob shape descriptors for those moving regions associated with movement of the user's head and hands. Alternatively, if the user's movement is tracked by locating the center of one or more pre-identified objects (e.g., a wrist or head band) in each frame of a video clip, the feature vector can contain the XY coordinates for the center of each tracked object and its derivatives.

Then, a gesture probability vector is obtained from the sequence of feature vectors (block 306). For each predefined gesture contained in a gesture vocabulary, the probability that the video clip contains that gesture is determined. The probabilities for all the gestures in the gesture vocabulary are then compiled in a gesture probability vector.

For example, the gesture probability vector can be generated using a bank of HMMs having at least one HMM for each gesture in the gesture vocabulary. Each HMM is trained using, for example, Baum-Welch training and a corpus of gesture prototypes for the gesture associated with that HMM. Recognition using the bank of HMMs is implemented using, for example, the Viterbi techniques and implementation-specific

heuristics. When the sequence of feature vectors for a given video clip is provided to the bank of HMMs, the evolution of each HMM obtains a probability that the video clip contains the gesture associated with that HMM. The probabilities  
5 generated by each of the HMMs in the bank are compiled in a gesture probability vector. Alternatively, other pattern recognition technologies such as neural networks or Bayesian classifiers can be used.

The gesture probability vector then can be used to  
10 determine if the video clip contains a gesture contained in the gesture vocabulary. FIG. 4 is a flow diagram of a process 400 for determining if the video clip contains a gesture contained in the gesture vocabulary. First, the gesture with the highest probability is identified from the gesture  
15 probability vector (block 402). If the highest probability exceeds a predefined threshold probability (which is checked in block 404) and exceeds the next highest probability in the gesture probability vector by a predefined amount (which is checked in block 406), then the video clip is considered to  
20 contain the gesture with the highest probability (block 408). If the highest probability does not exceed the predefined threshold probability or does not exceed the next highest probability by a predefined amount, then the recognition engine is considered to be confused (block 410). When the

recognition engine is confused, the video clip is considered not to include any gesture from the gesture vocabulary.

FIG. 5 is a block diagram of a system 500 that can be used to implement the gesture recognition process 100. The system 500 includes a video source 502 that provides video data of a user's movements. For example, the video source 502 can include a video camera or other device that provides "live" (that is, real time) video data of the user's movement. In addition or instead, the video source 502 can include a video storage and retrieval device such as a video cassette recorder ("VCR") or digital video disk ("DVD") player that provides previously captured video data of the user's movements.

The system 500 also includes a timing data source 504. The timing data source 504 provides timing data that is used to define a window in which a user is expected to perform a desired gesture. For example, in the embodiment shown in FIG. 5, the timing data is a function of an audio signal having a beat. The system 500 also can include a speaker 506 or other device that plays the audio signal so that the user can hear the audio signal and perform a gesture on the beat of the audio signal.

The audio signal can be provided by an audio source 508 included in the timing data source 504. The audio source 508

can include any device that provides an audio signal. For example, the audio source 508 can include an audio synthesizer and/or a compact disk or other audio media player.

Alternatively, the audio source 508 and the video source 502  
5 can be combined in a single device, such as a video camera, that provides both the audio signal and the video data. The audio signal provided by the audio source 508 is provided to a beat extractor 510. The beat extractor 510 generates the timing data by extracting beat data from the audio signal.

10 For example, the beat data can include the beat frequency of the audio signal. The beat frequency can be used to define the window in which the user is expected to perform a desired gesture, for example, by centering the window about the beat.

Beat data can be extracted from the audio signal using a  
15 variety of techniques. For example, if the audio signal is a musical industry digital interface ("MIDI") signal, the beat data can be generated from channel 10 of the MIDI audio signal, which defines a drum part of the signal. The frequency and phase information included in channel 10 of such  
20 a MIDI audio signal can be used to determine when a beat is going to occur in the audio signal. Other beat tracking and/or prediction techniques can also be used to extract beat data from the audio signal. An example of a suitable beat prediction technique is described in Eric D. Scheirer, "Tempo

and Beat Analysis of Acoustic Musical Signals," Journal of the Acoustical Society of America, volume 103, number 1, January 1998. Beats can also be manually obtained offline.

The system 500 also includes a recognition subsystem 512.

5 The recognition subsystem 512 includes a temporal segmentor 514 that receives the video data from the video source 502 and segments the video data into video clips based on the timing data. Each video clip contains that portion of the video data corresponding to a single window in which the user is expected  
10 to perform a desired gesture. The temporal segmentor 514 uses the timing data to determine where each window begins and/or ends in order to segment the video data into video clips.

The audio signal, video data, and timing data are synchronized so that the user is prompted to perform the  
15 desired gesture when expected by the recognition subsystem 512. The video source 502, timing data source 504, speaker 506, and temporal segmentor 514 are synchronized so that, for a given video clip, the timing data for that video clip (that is, the timing data that is used to identify the beginning  
20 and/or end of the window for that video clip) is extracted from the audio signal and provided to the temporal segmentor 514 in time to allow the temporal segmentor 514 to segment the video clip.

The recognition subsystem 512 also includes a feature extractor 516. The feature extractor 516 generates a feature vector for each frame of the video clip. For example, as noted above, the features vectors can be generated by  
5 generating position and motion information and blob shape descriptors for those moving blobs associated with the movement of the user's head and hands. Alternatively, the feature vectors can be generated by determining the XY coordinates for the center of one or more tracked objects  
10 (e.g., wrist and/or head bands worn by the user).

The feature vectors for each video clip are supplied to a recognition engine 518. For each predefined gesture included in a gesture vocabulary, the recognition engine 518 determines the probability that the video clip contains the predefined  
15 gesture. These probabilities can be combined into a gesture probability vector. The recognition engine 518 can be implemented using any pattern recognition technology including, for example, a bank of HMMs, neural networks, or Bayesian classifiers.

20 The gesture probability vectors produced by the recognition engine 518 can be supplied to an application 520. The application 520 can then use the gesture probability vector to determine which, if any, gesture from the gesture

vocabulary is contained in the video clip, for example, in accordance with process 400.

The system 500 can be implemented in software, hardware, or a combination of software and hardware. For example, the system 500 can be implemented using a general-purpose computer programmed to implement the components of the system 500. A video camera can be connected to the general-purpose computer in order to provide video data to the system 500. In other embodiments, the system 500 can be implemented using other information appliances such as special-purpose computers, game consoles, and PDAs.

The system 500 allows the user to provide gesture-based input to an application 520 without using specialized controllers or sensors that are physically connected to the system or the user. The user is untethered and can move freely while providing input to the system 500 as long as the user remains within the video camera's range and field of view. Thus, the system 500 can be implemented in an exercise system in which the movements made by the user in providing gesture-based input to the system 500 give the user an aerobic workout. Also, the system 500 can be implemented so that users of all sizes and shapes can provide input to the system 500, without requiring use of different controllers for different users. The system 500 can be used in a wide range

of embodiments. For example, the system 500 can be used in game and exercise systems (e.g., dance, music, and sports simulation games).

In one embodiment, the system 500 is used in a dance competition game system 600, which is shown in FIG. 6.

Generally, the dance competition game system 600 prompts the user to perform various dance moves on the beat of music played for the user. The user scores points by successfully performing the requested dance moves on the beat of the music.

The dance competition game system 600 includes a timing data source 602, which includes an audio source 604 and a beat extractor 606. The audio source 604 provides the music in the form of an audio signal that is sent to a speaker 608, which plays the music for the user. The audio signal is provided to the beat extractor 606, which extracts beat data from the audio signal, as described above.

The beat data that is extracted from the audio signal is supplied to a move sequence subsystem 610 and a recognition subsystem 612. The move sequence subsystem 610 includes a move sequence database 614. Dance moves that the user is expected to perform are retrieved from the database. Each dance move that is retrieved from the move sequence database 614 is placed into a move FIFO queue 616. The move FIFO queue 616 contains the next X dance moves the user is to perform on

the next X beats of the music. Icons or other data (e.g., text descriptions) representing the next X dance moves are displayed on a game display 618 that is connected to the move FIFO queue 616.

5 One example of a game display 618 is shown in FIGS. 7A-7B. The game display 618 includes a dance move region 702, a score region 704, and an avatar region 706. Pairs of icons 708, 710, 712, and 714 represent the next four dance moves the user is to perform on the next four beats of the music (i.e., X equals four). In the example shown in FIGS. 7A-7B, each pair of icons includes a left icon, which represents the direction in which the user is to point the user's left arm, and a right icon, which represents the direction in which the user is to point the user's right arm. For example, the top pair of icons 708 indicates that the user is to point the user's left arm to the left, while pointing the user's right arm to the right.

The icons 708, 710, 712, and 714 are displayed in the dance move region 702 in the order in which the dance moves associated with those icons are to be performed by the user. Thus, the user can determine which dance move the user is to perform next by looking at the top 716 of the dance move region 702 of the display 618. The user can determine which dance moves the user is to perform on the next three

successive beats of the music by looking at the icons 710, 712, and 714, displayed beneath the top pair of icons 708.

As shown in FIG. 7B, after the next beat of the music has occurred, the top pair of icons 708 is removed from the dance move region 702 and each of the other pairs of icons 710, 712, and 714 is scrolled up on the dance move region 702. A new pair of icons 720 representing the dance move added to the tail of the move FIFO queue 616 is also displayed at the bottom 722 of the dance move region 702.

The move region 702 of the game display 618 also can include a beat indicator 703. The beat indicator 703 provides a visual indication of the beat data. For example, the beat indicator 703 can be implemented as a blinking square that blinks to the beat of the music (i.e., based on the beat data extracted from the music by the beat extractor 606).

The user's actions are captured by a video camera 611 (shown in FIG. 6), which supplies video data to the recognition subsystem 612. The recognition subsystem 612 includes a temporal segmentor 620, a feature extractor 622, and a recognition engine 624. The temporal segmentor 620 segments the video data received from the video camera 611 into video clips based on the beat data. Each video clip is associated with a window in which the user is to perform a given dance move. Each video clip is provided to the feature

extractor 622, which generates a feature vector for each video frame contained in the video clip. The feature vectors for a given video clip are then provided to the recognition engine 624, which generates a gesture probability vector based on a predefined gesture vocabulary. The predefined gesture vocabulary includes each of the dance moves that the user may be asked to perform by the system 600. That is, the gesture vocabulary includes each of the dance moves contained in the move sequence database 614. The recognition engine 624 can be implemented as a bank of HMMs, with one HMM associated with each gesture in the gesture vocabulary. Each HMM calculates the probability that the video clip contains the gesture associated with that HMM. The probabilities generated by each of the HMMs in the bank are combined to create the gesture probability vector for that video clip.

The gesture probability vectors produced by the recognition subsystem 612 are provided to a scoring subsystem 626. The scoring subsystem 626 also checks if the dance move contained in the video clip was the dance move the user was requested to perform on the beat during the window associated with that video clip. If the video clip contains the requested dance move, the user scores points. The user's current score is displayed on the game display 618. For example, as shown in FIGS. 7A-7B, the user's score 724 is

displayed in the score region 704 of the game display 618. If the user successfully performs the dance move associated with the top pair of icons 708 on the next beat, then the user's score 724 is increased, as shown in FIG. 7B.

5           The game display 618 can also display an avatar. The avatar is an animated, graphical representation of the user or some other person. In one embodiment, the avatar can be rendered, performing the dance move the gesture recognition subsystem 612 determines that the user has performed during  
10           the most recent window. For example, as shown in FIGS. 7A-7B, the game display 618 can include an avatar 726 that is displayed in the avatar region 706 of the game display 618. If the user performs the dance move associated with the top pair of icons 708 on the next beat in the music, the avatar  
15           726 is shown performing that dance move. If the user performs a dance move that is recognized by the system 600 but not the dance move the user was requested to perform, the avatar 726 can be displayed performing the recognized dance move. If the recognition subsystem 612 is unable to recognize the move  
20           performed by the user, the avatar can be shown performing a default gesture that indicates to the user that the system was unable to recognize the move performed by the user.

A number of embodiments of the invention have been described. Nevertheless, it will be understood that various

modifications may be made without departing from the spirit and scope of the invention. For example, elements described as being implemented in hardware can also be implemented in software and/or a combination of hardware and software.

- 5 Likewise, elements described as being implemented in software can also be implemented in hardware and/or a combination of hardware and software. Accordingly, other embodiments are within the scope of the following claims.

**WHAT IS CLAIMED IS:**

1           1.    A method comprising:  
2                   segmenting video data to create a video clip based  
3   on timing data; and  
4                   determining a most likely gesture in the video clip.

1           2.    The method of claim 1, wherein determining includes  
2   determining a probability that each of a plurality of  
3   predefined gestures are performed in the video clip contains  
4   the predefined gesture.

1           3.    The method of claim 2, wherein determining the  
2   probability that the video clip contains each of the  
3   predefined gesture includes evaluations of Hidden Markov  
4   Models.

1           4.    The method of claim 1, wherein the timing data  
2   includes beat data corresponding to a beat of audio data.

1           5.    The method of claim 4, further comprising:  
2                   receiving the audio data; and  
3                   extracting the beat data from the audio data.

1           6.    The method of claim 4, wherein the video clip  
2   includes a portion of the video data corresponding to a  
3   predefined time window surrounding the occurrence of at least  
4   one beat.

1           7.    The method of claim 1, further comprising displaying  
2   a target gesture to be performed by the subject of the video  
3   data.

1           8.    The method of claim 1, wherein each video clip  
2   contains video frames.

1           9.    The method of claim 1, further comprising  
2   identifying moving regions in each video frame in the video  
3   clip.

1           10.   The method of claim 9, further comprising generating  
2   a feature vector for each video frame of the video clip.

1           11.   The method of claim 1, further comprising generating  
2   a score based on whether the video clip contains the target  
3   gesture.

1           12.   The method of claim 11, further comprising  
2   displaying the score.

1           13.   The method of claim 1, wherein determining if the  
2   video clip contains the predefined gesture includes generating  
3   a gesture probability vector having a plurality of elements,  
4   each element being associated with one of a plurality of  
5   predefined gestures and representing a probability that the

6 video clip contains each of the associated predefined  
7 gestures.

1 14. A system comprising:  
2 a temporal segmentor connected to receive video data and  
3 to create a video clip from the video data based on timing  
4 data; and  
5 a recognition engine, in communication with the temporal  
6 segmentor, to determine if the video clip contains a  
7 predefined gesture.

1 15. The system of claim 14, wherein the recognition  
2 engine includes a plurality of Hidden Markov Models.

1 16. The system of claim 14, further comprising:  
2 a timing data source, in communication with the temporal  
3 segmentor, to provide the timing data to the temporal  
4 segmentor; and  
5 a video source, in communication with the temporal  
6 segmentor, to provide the video data to the temporal  
7 segmentor.

1 17. The system of claim 14, further comprising a move  
2 subsystem, in communication with the timing data source, to  
3 provide a target gesture to be performed by the subject of the  
4 video data.

1           18. The system of claim 17, wherein the target gesture  
2 is a dance move that is to be performed by the subject of the  
3 video data.

1           19. The system of claim 17, further comprising a scoring  
2 subsystem, in communication with the recognition engine and  
3 the move subsystem, to determine if the video clip contains  
4 the target gesture.

1           20. The system of claim 19, further comprising a display  
2 subsystem, in communication with the scoring subsystem, to  
3 display a score that is a function of whether the video clip  
4 contains the target gesture.

1           21. The system of claim 20, wherein the display  
2 subsystem is in communication with the move subsystem and is  
3 configured to display a gesture request based on the target  
4 gesture.

1           22. The system of claim 14, wherein the recognition  
2 engine is configured to recognize predefined gestures and to  
3 produce a gesture probability vector having elements, each  
4 element being associated with one of the predefined gestures  
5 and representing the probability that the video clip contains  
6 the associated predefined gesture.

1        23. The system of claim 14, wherein the timing data  
2 source includes:

3        an audio source that provides an audio data; and  
4        a beat extractor, in communication with the audio source,  
5 that extracts beat data from the audio data.

1        24. The system of claim 23, wherein the video clip  
2 corresponds to a beat in the beat data.

1        25. The system of claim 24, wherein the video clip  
2 includes a portion of the video data corresponding to a  
3 predefined time window surrounding the occurrence of the beat.

1        26. A computer program product, tangibly stored on a  
2 computer-readable medium, for recognizing gestures contained  
3 in video data, comprising instructions operable to cause a  
4 programmable processor to:

5                segment the video data to create a video clip based  
6 on timing data; and

7                determine if the video clip contains a predefined  
8 gesture.

1        27. The product of claim 26, further comprising  
2 instructions operable to cause the programmable processor to:

3        extract beat data from an audio signal; and

4 segment the video data to create the video clip using the  
5 beat data.

1 28. An audio-visual processing system including:  
2 a video source to provide video data;  
3 an audio source to provide audio data;  
4 a speaker to play at least a portion of the audio data;  
5 and  
6 a computer program product, tangibly stored on a  
7 computer-readable medium, for recognizing gestures contained  
8 in video data, comprising instructions operable to cause a  
9 programmable processor, in communication with the video source  
10 and the audio source, to:  
11 extract beat data from the audio data;  
12 segment the video data to create a video clip based  
13 on beat data; and  
14 determine if the video clip contains a predefined  
15 gesture.

1 29. The video processing system of claim 28, wherein the  
2 computer program product further includes instructions  
3 operable to cause the programmable processor to:  
4 perform a Hidden Markov Model process to determine if the  
5 video clip contains the predefined gesture.

1           30. The video processing system of claim 28, further  
2   comprising a display to display information based on whether  
3   the video clip contains the predefined gesture.

**ABSTRACT**

Gesture recognition in which timing data is used to temporally segment video data into video clips. The timing data can be beat data extracted from an audio signal.





FIG. 1

200



~~to~~ in the picture.

~~No~~ FIFO

FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6

005160632560




FIG. 7A

00550629-094500




FIG. 7B